

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 November 2001 (29.11.2001)

PCT

(10) International Publication Number
WO 01/89335 A1

(51) International Patent Classification⁷: **A43B 7/20**,
3/02, 5/14

Gabriele [IT/IT]; Via Marosticana, 33, I-31010 Coste di Maser (IT).

(21) International Application Number: PCT/EP01/05284

(74) Agents: AGOSTINI, Agostino et al.; Dragotti & Associati S.r.l., Via Paris Bordone, 9, I-31100 Treviso (IT).

(22) International Filing Date: 9 May 2001 (09.05.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MI2000A001137 23 May 2000 (23.05.2000) IT

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(71) Applicant (*for all designated States except US*):
ALPINESTARS RESEARCH S.R.L. [IT/IT]; Via De Gasperi, 54, I-31010 Coste di Maser (IT).


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **MAZZAROLO,**

[Continued on next page]

(54) Title: STRUCTURE FOR LIMITING MOVEMENTS OF THE LEG-PIECE OF A MOTORCYCLE BOOT



(57) Abstract: Structure, associated with a motorcycle boot, which is designed to restrict, in the event of accidental falls followed by contact at high speed with the ground, the movements of the leg-piece (12) of the boot with respect to the axis of a heel-piece (14). First hinging means (16) which are angularly movable in a substantially unlimited manner and axially movable between two stopping means and second hinging means (18) which are movable only angularly in a restricted manner. Alternatively, the first and second hinging means can be formed by elements (176, 178) made of elastomeric materials.

WO 01/89335 A1



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

10 **STRUCTURE FOR LIMITING MOVEMENTS OF THE LEG-PIECE OF A MOTORCYCLE
BOOT**

* * * * *

15 The present invention relates to a structure intended for restricting the movements in the main directions, i.e. longitudinal, rotary and torsional directions, of the leg-piece of an a boot with respect to the axis of an associated heel-piece in order to protect a motorcyclist's lower limbs .

20 The dangers of severe injuries deriving from accidental impacts and falls are well known by people who practise motorcycling. The injuries can often involve the lower limbs, in particular the feet, and result from seemingly trivial manoeuvres or accidents, like setting a foot on the ground while the vehicle is travelling at high speed. In these circumstances the foot is subjected to severe stresses and, if it were not protected, quite severe consequences, such as fractures or other damages to the bones, and tearing of the Achilles tendon or of the ligaments in the region of malleoli would take place.

25 A need therefore exist of preventing, or at least limiting as far as possible, the said injuries which is satisfied by conventional boots comprising a rigid shell, enclosing the foot, and a leg-piece which is also rigid - enclosing the leg and hinged on the shell. During an accident these parts are obviously positioned between the limb to be protected and the obstacles encountered with the result of dampening the impacts and deflecting their action.

30 Even if motorcycle boots of this type are already available which greatly limit the possibility of bone fractures in the leg and foot and, when they are designed so as to surround at a sufficient extent the limb, are suitable for the protection against excessive torsional angles, no structure is presently available which is capable of restricting certain relative

movements of the foot and leg during a motorcycling accident that lead to excessive bending angles between the foot and the leg, either in the forward or backward direction.

The main object of the present invention is therefore to disclose a structure for the use in a motorcycle boot which is capable of restricting the relative movements, especially the rotary movements, between the foot and the leg to be protected.

The above mentioned object is achieved by a structure according to the present invention comprising : at least one leg-piece, close to and hinged on at least one heel-piece forming part of a rigid shell, characterized in that, close to the heel and between the leg-piece and the heel-piece first hinging means are provided which are angularly movable at a substantially unlimited extent as well as axially movable between two stopping means, and second hinging means which are permitted only a restricted angular movement.

The other characterizing features of the invention will be found in the appended subclaims. All the features and the consequent advantages of the invention will emerge more clearly from the following detailed description of some embodiment thereof and from the attached drawings in which :

- Figure 1 is a side elevation view of the protective part of a boot according to a first embodiment of the present invention;

- Figure 2 is similar to Figure 1 but refers to a second embodiment;

- Figure 3 is similar to Figures 1 and 2 but refers to a third embodiment;

- Figure 4 and 5 also refer to the said third embodiment and illustrate respectively a partial perspective view of the structure and a partial cross-sectional view of a bridge-piece, formed in the heel-piece, which is suitable to receive an arched tongue, connected to the leg-piece of the second hinging means;

- Figure 6 is similar to Figures 1 to 3 but refers to a fourth embodiment;

- Figure 7 also refers to the said fourth embodiment and is a partial cross-sectional view of a tongue and pocket assembly, having a spherical shape, to realise the second hinging means thereof; and

- Figure 8 is a perspective view of a fifth embodiment in which use is made of hinging means of elastomeric materials.

in the embodiment of Figure 1 a structure 10, to be associated with a motorcycling boot (not shown), consists of a leg-piece 12 connected to a heel-piece 14 by means of first rear hinging means 16 and second front hinging means 18. The said first hinging means 16

consist of a fastening stud 20 having a shank 22, an outer enlarged head 24 and an inner enlarged head 26, the shank 22 passing through an axially elongated eyelet 28 provided in the leg-piece 12. The second hinging means 18 comprise a front lug 30 in the lowermost portion of the leg-piece 12, an associated lug 32 in the heel-piece 14 and a stud 34, basically similar to the already mentioned stud 20, which has a narrow shank (not shown), an outer enlarged head 36 and an inner enlarged head (also not shown). The shank of the stud 34 passes through two holes, one in the lug 32 of the heel-piece 14 and another hole 38 in the lug 30 of the leg-piece 12. While the hole in the heel-piece 14 has substantially the same diameter as the shank of the stud 34, the hole in the leg-piece 12 is decidedly bigger than the same shank, although smaller than the outer enlarged head 36. As a consequence a movement is permitted of the lug 30 of the leg-piece 12 with respect to the lug 32 of the heel-piece 14 within the limits set by the mentioned difference in diameter between the hole 38 and the shank of the stud 34.

It shall be appreciated that due to the first hinging means 16 any relative angular movement is allowed between an axis of the leg-piece 12 and an axis of the heel-piece 14 but only an axial movement (namely along the longitudinal axis of the leg-piece 12) is possible within the limits set by the elongated eyelet 28 provided in the leg-piece 12 to the travel of the shank 22 of the stud 20. The relative angular movement between the axes of the leg-piece 12 and the heel-piece 14 is restricted by the said second hinging means 18 which only permit the shank of the stud 34 to move in the backlash between the same and the edges of the hole 38 provided in the lug 30 of the leg-piece 12. Any relative movements in a radial direction between the first hinging means 16 and the second hinging means 18 is substantially prevented by the stud 20 which secures the heel-piece 14 to the leg-piece 12. In this manner, in case of impacts, only restricted relative opening and closing movements of the leg-piece 12 and the heel-piece 14 are permitted, thus reducing the risk of the worst injuries which might occur to the Achilles tendon, the malleolar joints and their ligaments.

In the second embodiment, as illustrated in Figure 2, a structure 50 to be associated with a motorcycle boot (not shown) consists of a leg-piece 52 connected to a heel-piece 54 by means of first rear hinging means 56 and second front hinging means 58. The first rear hinging means 56 are the same as in the preceding embodiment, namely consist of a fastening stud 60 with a shank 62, an outer enlarged head 64 and an inner enlarged head 66, the shank 62 passing through an axially elongated eyelet 68 provided in the leg-piece 52. As

regards the second hinging means 58, the front lug 70 in the lowermost portion of the leg-piece 52, the associated lug 72 in the heel-piece 54, the stud 74, which has a narrow shank (not shown), an outer enlarged head 76 and an inner enlarged head (also not shown) also are the same as in the embodiment illustrated in Figure 1. Anyhow, of the two holes which are passed by the shank of the stud 74, the hole provided in the lug 72 of the heel-piece 54 substantially has the same diameter as the shank of the stud 74, while the second hole 78, which is provided in the front lug 70 of the leg-piece 52 and has the shape of an oblong eyelet with the shape of an arc having a radius R and an amplitude α , is longer than the said diameter. As a consequence, the second hinging means 58 allow a movement of the leg-piece 52 with respect to the heel-piece 54 along the arched hole 78.

It shall be appreciated from Figure 2 that due to the first hinging means 56 can allow any relative angular movement is allowed between an axis of the leg-piece 52 and an axis of the heel-piece 54 but only an axial movement (namely along the longitudinal axis of the leg-piece 52) is possible within the limits set by the oblong eyelet 68 to the travel of the shank 62 of the stud 60. The relative angular movement between the axes of the leg-piece 52 and of the heel-piece 54 is restricted by the second hinging means 58 which restrict the travel of the shank of the stud 74 to the angle α along the arched hole 78 provided in the lug 70 of the leg-piece 52. Movements in the radial direction are completely prevented because the shape of the hole 78 prevents variations in the radius R of the arch A . This second embodiment of the invention proves even more effective than the first embodiment as to the limitation of the injuries which might occur to the Achilles tendon, the malleolar joints and their ligaments.

With reference now to Figures 3, 4 and 5 which illustrate a third embodiment of the invention, a structure 90, to be associated with a motorcycle boot, consists of a leg-piece 92 connected to a heel-piece 94 by means of a first rear hinging means 96 and a second front hinging means 98. As in both embodiments already described, the first hinging means 96 consist of a fastening stud 100 having a shank 102, an outer enlarged head 104 and an inner enlarged head 106, the shank 102 passing through an axially elongated eyelet 108 provided in the leg-piece 92. However, the second hinging means 98, positioned between a lug 110 of the leg-piece 92 and an underlying lug 112 of the heel-piece 94, consist of an arched tongue 114, of a mean radius R , connected to the lug 110 by two abutments 116 and passing under a bridge-piece 118 obtained by an upraised portion of the heel-piece 94, as is shown in detail in Figures 4 and 5. The bottom end 120 of the arched tongue 114, which is thicker, prevents

the tongue 114 from coming out of the bridge-piece 118. The shape and the length of the tongue 114 allow a movement of the leg-piece 92 with respect to the heel-piece 94 along the mean line A of the tongue 114 which is restricted at the top by the abutments 116 and at the bottom by the thicker end 120.

5 It shall be appreciated that in the third embodiment illustrated in Figures 3, 4 and 5 the hinging means 96 allow any relative angular movement between an axis of the leg-piece 92 and an axis of the heel-piece 94 but only an axial movement (namely along the longitudinal axis of the leg-piece 92) restricted by the travel of the shank 102 in the elongated eyelet 108 formed in the leg-piece 92. The relative angular movement between the axes of the leg-piece
10 92 and the heel-piece 94 is restricted by the hinging means 98 which limit the travel of the arched tongue 114 to the length of the mean line A, of a radius R, defined between the shoulders 116 and the thicker zone 120. Movements in the radial direction are completely prevented since the shape of the tongue 114 under the bridge-piece 118 prevents any variation of the said radius R. The efficiency of the third embodiment of the invention is
15 substantially the same as the efficiency of the second one, illustrated in Figure 2, as regards the limitation of the injuries which may occur to the Achilles tendon, the malleolar joints and their ligaments. However, the elimination of studs in the hinging means 98 - which may penetrate into the foot or the leg - bears the additional advantage of making the structure even safer in the event of impacts which cause the deformation of the leg-piece 92 or the heel-piece
20 94.

With reference to Figures 6 and 7 illustrating a fourth embodiment of the invention, a structure 130, to be associated with a motorcycle boot, consists of a leg-piece 132 connected to a heel-piece 134 by means of first rear hinging means 136 and second front hinging means 138. As in the previously described three embodiments, the first hinging means 136 consist of
25 a fastening stud 140 with a shank 142, an outer enlarged head 144 and an inner enlarged head 146, the shank 142 passing through an axially elongated eyelet 148 provided in the leg-piece 132. However, the second hinging means 138, positioned between a lug 150 of the leg-piece 132 and an underlying lug 152 of the heel-piece 134, are formed by an arched tongue 154, of a mean radius R, which can be joined to the lug 150 by two widened zones 156 and
30 inserted in a pocket 161, which is formed inside the lug 152 of the heel-piece 134 by two adjacent walls 158 and 160 joined in a zone 162 so as to form the bottom of a pocket, as is shown in detail in Figure 7.

It shall be appreciated from Figures 6 and 7 that the hinging means 136 allow any relative angular movement between an axis of the leg-piece 132 and an axis of the heel-piece 134 but only an axial movement (namely along the longitudinal axis of the leg-piece 132) restricted by the travel of the shank 142 in the elongated eyelet 148 provided in the leg-piece 132. The relative angular movement between the axes of the leg-piece 132 and the heel-piece 134 is restricted by the hinging means 138 provided that during closing the travel of the arched tongue 154 is restricted to the length of the mean line A, of a radius R, defined between the two widened zones 156 and the bottom 162 of the pocket 161 of the heel-piece 134 and during opening the travel is dampened owing to the spherical curved shape of the tongue 154 which rubs against adjacent walls 158 and 160. Movements in the radial direction are completely prevented because the shape of the tongue 154 inside the pocket under the bridge-piece 118 prevents any variation of the radius R. This embodiment of the invention is substantially as effective as the third one, illustrated in Figures 3, 4 and 5, as regards the limitation of the injuries which may occur to the Achilles tendon, the malleolar joints and their ligaments. In addition, the dampened angular travel during opening of the arched tongue 154 entails a gradual resistance to the opening movement instead of a harsh stop as provided by the thicker bottom end 120 of the arched tongue 114 in the previous embodiment.

In a final embodiment of the invention, illustrated in Figure 8, which is notable because of its simplicity, a structure 170, to be associated with a motorcycle boot, consists of a leg-piece 172 connected to a heel-piece 174 by means of first rear hinging means 176 and second front hinging means 178. Both the rear and front hinging means 176 and 178 consist of moulded parts made of elastomeric materials to realize the connection between the leg-piece 172 and the heel-piece 174 in the region of the heel and of the inner side of the ankle joint. The restrictions to axial and angular movements of the two hinging means 176 and 178 are ensured by the physical characteristics of the elastomeric materials chosen for their construction since they are able to offer a sufficient protection against injuries involving the Achilles tendon, the malleolar joint and ligaments. This construction is also remarkable for a decidedly lower cost than the four embodiments illustrated in Figures 1 to 7.

Moreover, it should be noted that the use of hinging means 176 and 178 made of elastomeric materials has the further advantage of not requiring any additional thicker zone on the leg-piece 172 and heel-piece 174. Consequently, the fifth embodiment of the invention allows simplifications in the design of an inner shoe, to be positioned between the structure

170, the leg and foot.

It is finally to remark that the above described embodiments of the invention shall not be considered in a limiting sense, the scope of the invention being defined only by the following claims.

CLAIMS

1. Structure, associated with a motorcycle boot, comprising at least one leg-piece (12, 52, 92, 132, 172), close to and hinged with at least one heel-piece (14, 54, 94, 134, 174) included in a rigid shell, characterized in that between the leg-piece (12, 52, 92, 132, 172) and heel-piece (14, 54, 94, 134, 174) first hinging means (16, 56, 96, 136, 176) are provided which are positioned close to the heel and are angularly movable in a substantially unlimited manner and are axially movable between two stopping means, and a second hinging means (18, 58, 98, 138, 178) which is angularly movable in a restricted manner.

2. Structure, according to Claim 1, characterized in that the first hinging means (16) consist of a first stud (20), for securing the leg-piece (12) to the heel-piece (14) in the region of the heel, which engages in two holes passing through the leg-piece and the heel-piece respectively, one of which said holes having the dimensions of the shank (22) of the said first stud (20) and the other (28) is in the shape of an eyelet elongated in the axial direction so as to allow a restricted movement in this latter direction, and the second hinging means (18) consist of a second stud (34), for securing the leg-piece (12) to the heel-piece (14) in the region of the malleolus, which engages in two holes, one of which has the dimensions of the shank of the said second stud (34) and the other (38) is wider than the same shank in such a way as to allow freedom of movement along an angularly restricted arc centred on the first hinging means (16).

3. Structure, according to Claim 2, characterized in that the hole (38) of the second hinging means (18), which is wider than the corresponding shank, is of a round shape in the region of the malleolus.

4. Structure, according to Claim 2, characterized in that the hole of the second hinging means (58), which is wider than the corresponding shank, is an oblong eyelet (78) with the shape of an arc (A) which is centred on the first hinging means (56) in the region of the malleolus.

5. Structure, according to Claim 1, characterized in that the second hinging means (98) consist of at least one tongue (114), in the shape of an arch (A) centred on the first hinging means (96), which is projecting from the leg-piece (92) and is slidable under a raised bridge-piece (118) protruding from the heel-piece (94), where the arched tongue (114) is provided with at least first upper stopping means (116), which restrict the angular movement during closing, and second lower stopping means (120) which restrict the movement during

opening.

6. Structure, according to Claim 5, characterized in that the upper stopping means consist of two widened zones (116) at the base of the arched tongue (114), which rest against the two outer ends of the said protruding bridge-piece (118), and the lower stopping means
5 consist of a thicker zone (120) of said arched tongue (114), which projects from the tip thereof and can be engaged against the bottom edge of same bridge-piece (118).

7. Structure, according to Claim 1, characterized in that the second hinging means (138) consist of at least one tongue (154) in the shape of an arch centred on the first hinging means (136), which is projecting from the leg-piece (132), is curved inwards as a
10 spherical zone and slidable into a pocket (161) having a shape matching that of the tongue (154) provided in the heel-piece (134), where the tongue (154) is provided with stopping means for the angular movement during closing and with a dampening system for the angular movement during opening.

8. Structure, according to Claim 7, characterized in that the stopping means for
15 the angular movement during closing consist of two widened zones (156) of the tongue (154) which engage against an upper edge of the pocket (161) and the dampening system for the angular movement during opening consists of the spherical-zone curvature of both the tongue (154) and the pocket (161).

9. Structure, according to Claim 7, characterized in that the stopping means for
20 the angular movement during closing is formed by the bottom (162) of the pocket (161) and the braking system for the angular movement during opening is formed by the spherical-shaped zones of both the tongue (154) and the pocket (161).

10. Structure, according to Claim 1, characterized in that the first hinging means
25 (176) between the leg-piece (172) and the heel-piece (174) consist of a first elastomer element made of an elastomeric material allowing a complete angular movement and a restricted axial movement and the second hinging means (178) consist of at least a second element made of an elastomeric material allowing only a restricted angular movement.

11. Structure, according to Claim 10, characterized in that the second hinging
30 means (178) consist of two elements made of elastomeric materials which are located on each side of the boot between the leg-piece (172) and the heel-piece (174) in the region of the malleolus.

1/5




FIG. 1







FIG. 2

3/5






FIG. 7

FIG. 6

5/5




FIG. 8

INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/EP 01/05284

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A43B7/20 A43B3/02 A43B5/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A43B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
E	FR 2 800 976 A (VALAT GERARD) 18 May 2001 (2001-05-18) the whole document	1
X	WO 98 31247 A (BARBER TED ;SAND JEFF WALDO (US); SWITCH MFG (US)) 23 July 1998 (1998-07-23) the whole document	1
X	EP 0 813 825 A (SHIMANO KK) 29 December 1997 (1997-12-29) the whole document	1
A	US 4 062 133 A (ROBRAN DAVID T ET AL) 13 December 1977 (1977-12-13) the whole document	1
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

25 October 2001

Date of mailing of the international search report

05/11/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Claudel, B

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 01/05284

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 656 776 A (ROSSIGNOL SA) 12 July 1991 (1991-07-12) the whole document -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 01/05284

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2800976	A	18-05-2001	FR 2800976 A1	18-05-2001
			AU 1712801 A	30-05-2001
			WO 0135781 A1	25-05-2001
WO 9831247	A	23-07-1998	AU 5733998 A	07-08-1998
			DK 102499 A	14-07-1999
			EP 0961555 A1	08-12-1999
			WO 9831247 A1	23-07-1998
			US 6082026 A	04-07-2000
EP 0813825	A	29-12-1997	EP 0813825 A1	29-12-1997
			DE 69601785 D1	22-04-1999
			DE 69601785 T2	08-07-1999
US 4062133	A	13-12-1977	AU 510628 B2	03-07-1980
			AU 2872177 A	22-03-1979
			CA 1066888 A1	27-11-1979
			DE 2740976 A1	23-03-1978
			FR 2397168 A1	09-02-1979
			GB 1583588 A	28-01-1981
			IT 1112108 B	13-01-1986
			JP 53038452 A	08-04-1978
			NL 7709985 A	15-03-1978
			SE 7710199 A	14-03-1978
FR 2656776	A	12-07-1991	FR 2656776 A1	12-07-1991

THIS PAGE BLANK (USFTO)